

## Cutbend the Original

---



More than 35,000 samples of the proven CUTBEND machine for cutting and bending the axial leads for taped components are operated worldwide. Thanks to its high performance (up to 25,000 components per hour) and its easy operation, this machine stands the test day after day. The machine amortizes in a short time thanks to its exceptional cost-effectiveness. The CUTBEND can easily be adjusted and readjusted to different components and dimensions. The easy-to-replace cutting and bending wheels allow very thin (0.5mm) or very thick (1.2mm) leads to be processed. The well-designed mechanism avoids axial tensile stress during processing and damage to delicate components by the slight staggering of the processing of both lead ends. The CUTBEND is handy and can be mounted to any table thanks to its screw clamp. The numerous accessories allow a full component processing system to be created on the basis of the CUTBEND



The adjustment tool supplied as standard equipment, used to transfer the distances between the holes of the board and for quick and accurate setting of the CUTBEND

## Technical Specifications

Dimensions (without crank): L 175 / W 145 / H 160mm Gross Weight:- 1.9kg

Crank Length:- 160mm

Output: up to 40,000 pcs per hour

Processing Possibilities:				
VB head type	A	B	C	D
● 0.5mm	0.3 - 0.5mm	4.7 - 40mm	Min - 1.0mm	2.6 - 15mm
□ 0.8mm	0.5 - 0.8mm	6.0 - 40mm	Min - 1.3mm	3.6 - 15mm
● 1.0mm	0.9 - 1.0mm	6.0 - 40mm	Min - 1.8mm	3.6 - 15mm
● 1.2mm	1.1 - 1.2mm	6.0 - 40mm	Min - 2.0mm	3.6 - 15mm

● FG head type


E
—
3.1 - 20mm
—
—

Maximum component diameter for all head types: 14mm


□ = Standard

● = Option

Standard equipment: cutting and bending on both sides (VB head)



Cutting and bending on one side (1/2 VB head)  
Cutting on the other side only (1/2 FG head = BG head)



Cutting on both sides only = FG head

